


MXH230

无限白金涂层 30°螺旋角 2刃平底铣刀
MUGEN-COATING PREMIUM 2-Flute LEAD30 End Mill



- 采用无限白金涂层，可适用于不锈钢、钛等耐热合金钢。
- 刃长为刃径的2倍，采用30°螺旋角。
- 可支持沟槽、侧面切削的标准型。
- Applicable for heat resistance alloy such as stainless steels and titanium alloy by MUGEN-COATING PREMIUM.
- L/D=2 and helix 30°standard type, applicable for both slotting and side milling.



加工材料 Work Material

碳素钢 Carbon Steels	合金钢·工具钢 Alloy Steels·Tool Steels	预硬钢·调质钢 Prehardened Steels	淬火钢 Hardened Steels		不锈钢 Stainless Steels	钛合金 Titanium Alloy	铝合金 Aluminum	铜合金 Copper	树脂 Plastic
			~55HRC	55HRC~					
○	○	○	○	○	◎	◎	○	○	○

单位 [规格: mm / 价格: 日元]
Unit [size: mm / Retail Price: JPY]

产品代码 Code No.	(D)刃径 Dia.	(L)刃长 Length of Cut	(γ)颈角 Neck Taper Angle	(d)柄径 Shank Dia.	(L)全长 Overall Length	定价(日元) Retail Price
08-00006-00010	0.1	0.2	12°	4	45	7,200
08-00006-00020	0.2	0.4	12°	4	45	4,600
08-00006-00030	0.3	0.6	12°	4	45	3,600
08-00006-00040	0.4	0.8	12°	4	45	4,200
08-00006-00050	0.5	1	12°	4	45	2,500
08-00006-00060	0.6	1.2	12°	4	45	3,500
08-00006-00070	0.7	1.4	12°	4	45	3,800
08-00006-00080	0.8	1.6	12°	4	45	2,500
08-00006-00090	0.9	1.8	12°	4	45	3,800
08-00006-00100	1	2	12°	4	45	2,200
08-00006-00110	1.1	2.2	12°	4	45	3,900
08-00006-00120	1.2	2.4	12°	4	45	2,500
08-00006-00130	1.3	2.6	12°	4	45	3,900
08-00006-00140	1.4	2.8	12°	4	45	3,900
08-00006-00150	1.5	3	12°	4	45	2,300
08-00006-00160	1.6	3.2	12°	4	45	3,900
08-00006-00170	1.7	3.4	12°	4	45	3,900
08-00006-00180	1.8	3.6	12°	4	45	2,500
08-00006-00190	1.9	3.8	12°	4	45	3,900
08-00006-00200	2	4	12°	4	45	2,300
08-00006-00210	2.1	4.2	12°	4	45	3,900
08-00006-00220	2.2	4.4	12°	4	45	3,900
08-00006-00230	2.3	4.6	12°	4	45	3,900
08-00006-00240	2.4	4.8	12°	4	45	3,900
08-00006-00250	2.5	5	12°	4	45	2,300
08-00006-00260	2.6	5.2	12°	4	45	5,000
08-00006-00270	2.7	5.4	12°	4	45	5,000

产品代码 Code No.	(D)刃径 Dia.	(L)刃长 Length of Cut	(γ)颈角 Neck Taper Angle	(d)柄径 Shank Dia.	(L)全长 Overall Length	定价(日元) Retail Price
08-00006-00280	2.8	5.6	12°	4	45	5,000
08-00006-00290	2.9	5.8	12°	4	45	5,000
08-00006-00300	3	6	12°	6	45	2,900
08-00006-00350	3.5	7	12°	6	45	4,400
08-00006-00400	4	8	12°	6	45	3,200
08-00006-00450	4.5	9	12°	6	50	5,000
08-00006-00500	5	10	12°	6	50	3,400
08-00006-00550	5.5	11	12°	6	50	5,000
08-00006-00600	6	12	—	6	50	3,700

订购方法

请指定MXH230 刃径(D).
When you order, indicate MXH230 (D).

※ (γ)为参考值。

※ (γ) is reference value.

● 切削参数表记载于第D-009页

● Recommended Milling Conditions are shown on page D-009.