

DCHR230

切削参数参考表 Recommended Milling Conditions

加工材料 Work Material		石墨 Graphite							铝合金压铸件 Aluminum Alloy Die Casting						
		等高线粗加工 Contour Line Roughing				沟槽切削 Slotting			等高线粗加工 Contour Line Roughing				沟槽切削 Slotting		
		主轴转速 Spindle Speed	进给速度 Feed	切深量 Depth of Cut		主轴转速 Spindle Speed	进给速度 Feed	切深量 Depth of Cut	主轴转速 Spindle Speed	进给速度 Feed	切深量 Depth of Cut		主轴转速 Spindle Speed	进给速度 Feed	切深量 Depth of Cut
min ⁻¹	mm/min	ap mm	ap mm	min ⁻¹	mm/min	ap mm	min ⁻¹	mm/min	ap mm	ap mm	min ⁻¹	mm/min	ap mm		
0.5	2	30,000	1,200	0.1	0.3	30,000	800	0.1	20,000	1,000	0.03	0.3	20,000	500	0.03
	4	30,000	1,000	0.05	0.3	30,000	600	0.05	20,000	800	0.01	0.3	20,000	400	0.01
	6	25,000	800	0.03	0.3	25,000	500	0.03	20,000	600	0.01	0.3	20,000	300	0.01
1	4	30,000	2,500	0.2	0.6	30,000	1,500	0.2	20,000	2,000	0.15	0.6	20,000	1,200	0.15
	6	25,000	2,000	0.2	0.6	25,000	1,200	0.2	20,000	1,500	0.1	0.6	20,000	1,000	0.1
	8	20,000	1,500	0.1	0.6	20,000	1,000	0.1	20,000	1,000	0.07	0.6	20,000	700	0.07
1.5	10	20,000	1,000	0.1	0.6	20,000	600	0.1	20,000	800	0.05	0.6	20,000	500	0.05
	6	25,000	2,500	0.3	1	25,000	1,600	0.3	20,000	2,000	0.2	1	20,000	1,500	0.2
	12	16,000	1,800	0.2	1	16,000	1,000	0.2	16,000	1,500	0.05	1	16,000	1,000	0.05
2	20	12,000	1,000	0.1	1	12,000	600	0.1	12,000	800	0.02	1	12,000	500	0.02
	6	20,000	3,000	0.5	1.2	20,000	2,000	0.5	20,000	2,000	0.5	1.2	20,000	1,500	0.5
	10	20,000	2,500	0.5	1.2	20,000	1,600	0.5	20,000	1,500	0.3	1.2	20,000	1,000	0.3
3	16	18,000	1,800	0.3	1.2	18,000	1,200	0.3	15,000	1,200	0.07	1.2	15,000	800	0.07
	20	15,000	1,200	0.2	1.2	15,000	800	0.2	10,000	1,000	0.03	1.2	10,000	600	0.03
	16	20,000	3,000	0.5	2	20,000	2,000	0.5	18,000	2,000	0.5	2	18,000	1,500	0.5
4	30	15,000	1,500	0.3	2	15,000	1,000	0.3	10,000	1,000	0.2	2	10,000	600	0.2
	20	18,000	3,000	0.8	2.5	18,000	2,000	0.8	16,000	2,000	0.8	2.5	16,000	1,500	0.8
	40	9,000	1,500	0.4	2.5	9,000	1,000	0.4	8,000	1,000	0.4	2.5	8,000	600	0.4
6	30	16,000	3,000	1	4	16,000	2,000	1	12,000	2,000	1	4	12,000	1,500	1

备注
Notes

※加工石墨时，请使用石墨专用的加工机床。
 此外，进行加工或者操作时为了防止粉尘飞扬或者被吸入身体，请使用吸尘器和防尘口罩。
 ※石墨加工建议采用干式切削。
 ※如果刀具发生崩刃，或者需要高精度加工时，请降低进给速度。
 ※发生振刀时，请以相同的比率降低主轴转速和进给速度。
 此外，主轴转速过低时，也以相同的比率降低。
 ※Graphite should be machined by the machining center designed for graphite machining.
 ※When handling with graphite material, dust collector and respirator are recommended to protect against graphite dust.
 ※Air blow cooling is recommended for the machining of graphite.
 ※Slow down the feed for high accurate machining to avoid breakage of work piece.
 ※Adjust both spindle speed and feed at the same rate when chattering.

PCD : 涂层 PCD-Monocoating	涂层 Coating	长头铣刀 Long Neck Spares	钻头铣刀 Diamond
涂层 Coating	无涂层 Non-Coating	平底铣刀 Square	长颈平底 铣刀 Long Neck Spares
涂层 Coating	无涂层 Non-Coating	球头铣刀 Ball	长颈球头 铣刀 Long Neck Ball
涂层 Coating	无涂层 Non-Coating	圆鼻铣刀 Radius	长颈圆鼻 铣刀 Long Neck Radius
涂层 Coating	无涂层 Non-Coating	锥形铣刀 Taper	锥形球头 铣刀 Taper Ball
涂层 Coating	无涂层 Non-Coating	锥形圆鼻 铣刀 Taper Radius	倒角刀 Chamfering
			钻头 Drilling
			螺纹铣刀 Thread milling
			倒角刀 Chamfering