


# MXH230P

无限白金涂层 30°螺旋角 2刃尖角型平底铣刀  
MUGEN-COATING PREMIUM 2-Flute Sharp Edge LEAD30 End Mill



- 采用无限白金涂层，可适用于不锈钢、钛等耐热合金的尖角型。
- 刃长为刃径的2倍，采用30°螺旋角。
- Applicable for heat resistance alloy such as stainless steels and titanium alloy by MUGEN-COATING PREMIUM with sharp edge type.
- L/D=2 and helix 30°.



### 加工材料 Work Material

碳素钢 Carbon Steels	合金钢·工具钢 Alloy Steels· Tool Steels	预硬钢·调质钢 Prehardened Steels	淬火钢 Hardened Steels		不锈钢 Stainless Steels	钛合金 Titanium Alloy	铝合金 Aluminum	铜合金 Copper	树脂 Plastic
○	○	○	~55HRC	55HRC~	◎	◎	○	○	○

单位 [规格: mm / 价格: 日元]  
Unit [size: mm / Retail Price: JPY]

产品代码 Code No.	(D)刃径 Dia.	(L)刃长 Length of Cut	(γ)颈角 Neck Taper Angle	(d)柄径 Shank Dia.	(L)全长 Overall Length	定价(日元) Retail Price
08-00016-00010	0.1	0.2	12°	4	45	7,200
08-00016-00020	0.2	0.4	12°	4	45	4,600
08-00016-00030	0.3	0.6	12°	4	45	3,600
08-00016-00040	0.4	0.8	12°	4	45	4,200
08-00016-00050	0.5	1	12°	4	45	2,500
08-00016-00060	0.6	1.2	12°	4	45	3,500
08-00016-00070	0.7	1.4	12°	4	45	3,800
08-00016-00080	0.8	1.6	12°	4	45	2,500
08-00016-00090	0.9	1.8	12°	4	45	3,800
08-00016-00100	1	2	12°	4	45	2,200
08-00016-00110	1.1	2.2	12°	4	45	3,900
08-00016-00120	1.2	2.4	12°	4	45	2,500
08-00016-00130	1.3	2.6	12°	4	45	3,900
08-00016-00140	1.4	2.8	12°	4	45	3,900
08-00016-00150	1.5	3	12°	4	45	2,300
08-00016-00160	1.6	3.2	12°	4	45	3,900
08-00016-00170	1.7	3.4	12°	4	45	3,900
08-00016-00180	1.8	3.6	12°	4	45	2,500
08-00016-00190	1.9	3.8	12°	4	45	3,900
08-00016-00200	2	4	12°	4	45	2,300
08-00016-00210	2.1	4.2	12°	4	45	3,900
08-00016-00220	2.2	4.4	12°	4	45	3,900
08-00016-00230	2.3	4.6	12°	4	45	3,900
08-00016-00240	2.4	4.8	12°	4	45	3,900
08-00016-00250	2.5	5	12°	4	45	2,300
08-00016-00260	2.6	5.2	12°	4	45	5,000
08-00016-00270	2.7	5.4	12°	4	45	5,000

产品代码 Code No.	(D)刃径 Dia.	(L)刃长 Length of Cut	(γ)颈角 Neck Taper Angle	(d)柄径 Shank Dia.	(L)全长 Overall Length	定价(日元) Retail Price
08-00016-00280	2.8	5.6	12°	4	45	5,000
08-00016-00290	2.9	5.8	12°	4	45	5,000
08-00016-00300	3	6	12°	6	45	2,900
08-00016-00350	3.5	7	12°	6	45	4,400
08-00016-00400	4	8	12°	6	45	3,200
08-00016-00450	4.5	9	12°	6	50	5,000
08-00016-00500	5	10	12°	6	50	3,400
08-00016-00550	5.5	11	12°	6	50	5,000
08-00016-00600	6	12	—	6	50	3,700

### 订购方法

请指定MXH230P 刃径(D).  
When you order, indicate MXH230P (D).

※ (γ)为参考值。

※ (γ) is reference value.

● 切削参数表记载于第D-014页

● Recommended Milling Conditions are shown on page D-014.